



**EMPRESA FUNDADA EN 1977**

**JUNTAMAS H°F°**

**CLASE AC C3 - H°F°**


| JUNTAMAS AC C3  | Ø   | Ø EXT. |
|---|-----|--------|
|  | 50  | 68     |
|   | 60  | 78     |
|   | 75  | 93     |
|   | 100 | 118    |
|   | 125 | 145    |
|   | 150 | 170    |
|   | 175 | 195    |
|   | 200 | 222    |
|   | 225 | 247    |
|   | 250 | 274    |
|   | 300 | 328    |
|   | 350 | 382    |
|   | 400 | 436    |
|   | 450 | 490    |
|   | 500 | 544    |
| 600   | 648 |        |

**CLASE AC C5 - H°F°**


| JUNTAMAS AC C5  | Ø   | Ø EXT. |
|---|-----|--------|
|  | 50  | 74     |
|   | 60  | 84     |
|   | 75  | 99     |
|   | 100 | 124    |
|   | 125 | 149    |
|   | 150 | 174    |
|   | 175 | 201    |
|   | 200 | 230    |
|   | 225 | 259    |
|   | 250 | 286    |
|   | 300 | 344    |
|   | 350 | 400    |
|   | 400 | 458    |
|   | 450 | 516    |
|   | 500 | 572    |
| 600   | 676 |        |

**EMPRESA FUNDADA EN 1977**


**CLASE PVC**

| JUNTAMAS PVC  | Ø   | Ø EXT. |
|---|-----|--------|
|  | 45  | 50     |
|   | 50  | 63     |
|   | 60  | 75     |
|   | 75  | 90     |
|   | 100 | 110    |
|   | 115 | 125    |
|   | 125 | 140    |
|   | 150 | 160    |
|   | 175 | 200    |
|   | 200 | 225    |
|   | 225 | 250    |
|   | 250 | 280    |
|   | 300 | 315    |
|   | 325 | 355    |
|   | 350 | 400    |
|   | 400 | 450    |
| 450   | 500 |        |

**CLASE AC C5-7**

| JUNTAMAS AC C5-7  | Ø   | Ø EXT. |
|---|-----|--------|
|  | 50  | 79     |
|   | 60  | 89     |
|   | 75  | 107    |
|   | 100 | 131    |
|   | 125 | 151    |
|   | 150 | 179    |
|   | 175 | 211    |
|   | 200 | 234    |
|   | 225 | 271    |
|   | 250 | 290    |
|   | 300 | 348    |
|   | 350 | 406    |
|   | 400 | 464    |
|   | 450 | 520    |
| 500   | 578 |        |
| 600   | 694 |        |


**CLASE AC C10**

| JUNTAMAS AC C10   | Ø   | Ø EXT. |
|---|-----|--------|
|  | 125 | 160    |
|   | 150 | 184    |
|   | 175 | 215    |
|   | 200 | 246    |
|   | 225 | 275    |
|   | 250 | 306    |
|   | 300 | 368    |
|   | 350 | 428    |
| 400   | 490 |        |


**EMPRESA FUNDADA EN 1977**

**TOMAS DE AGUA VERSION H°F°**

**CLASE AC C3 - H°F°**

| T/AGUA P/CANO DE H°F°   | Ø   | Ø EXT. | SALIDA  |
|---|-----|--------|---------|
|  | 50  | 68     | ½ / ¾   |
|   | 50  | 68     | 1       |
|   | 60  | 78     | ½ / ¾   |
|   | 60  | 78     | 1       |
|   | 75  | 93     | ½ / ¾   |
|   | 75  | 93     | 1       |
|   | 100 | 118    | ½ / ¾   |
|   | 100 | 118    | 1       |
|   | 150 | 170    | ½ / ¾   |
|   | 150 | 170    | 1       |
|   | 200 | 222    | ½ / ¾   |
|   | 200 | 222    | 1       |
|   | 200 | 222    | 2       |
|   | 250 | 274    | ½ / ¾   |
|   | 250 | 274    | 1       |
|   | 250 | 274    | 1 ¼ / 2 |
|   | 300 | 328    | ½ / ¾   |
|   | 300 | 328    | 1       |
|   | 300 | 328    | 2       |
|   | 350 | 382    | ½ / ¾   |
| 350   | 382 | 1      |         |
| 350   | 382 | 2      |         |

**CLASE AC C5**

| T/AGUA P/CANO DE AC   | Ø   | Ø EXT. | SALIDA |
|---|-----|--------|--------|
|  | 50  | 74     | ½ / ¾  |
|   | 50  | 74     | 1      |
|   | 60  | 84     | ½ / ¾  |
|   | 60  | 84     | 1      |
|   | 75  | 99     | ½ / ¾  |
|   | 75  | 99     | 1      |
|   | 100 | 124    | ½ / ¾  |
|   | 100 | 124    | 1      |
|   | 125 | 149    | ½ / ¾  |
|   | 125 | 149    | 1      |
|   | 150 | 174    | ½ / ¾  |
|   | 150 | 174    | 1      |
|   | 175 | 201    | ½ / ¾  |
|   | 175 | 201    | 1      |
|   | 200 | 230    | ½ / ¾  |
|   | 200 | 230    | 1      |
|   | 200 | 230    | 2      |
|   | 250 | 286    | ½ / ¾  |
|   | 250 | 286    | 1      |
|   | 250 | 286    | 2      |
|   | 300 | 344    | ½ / ¾  |
|   | 300 | 344    | 1      |
|   | 300 | 344    | 2      |
|   | 400 | 458    | ½ / ¾  |
|   | 400 | 458    | 1      |
| 400   | 458 | 2      |        |



CAÑOS - ACCESORIOS - VALVULAS

Brandsen 2479 C.P. 1702 - José Ingenieros  
Buenos Aires - Argentina  
Teléfono: (54-11) 4757-3204/6004/1618  
FAX Directo: 4 7 1 2 - 5 7 5 4  
Info@canopol.com / www.canopol.com

ISO 9001

BUREAU VERITAS  
Certification



**EMPRESA FUNDADA EN 1977**

**TOMAS DE AGUA VERSION H°F°**

**CLASE PVC**

| T/AGUA P/CAÑO DE PVC | Ø   | Ø EXT. | SALIDA    |
|----------------------|-----|--------|-----------|
|                      | 35  | 40     | ½ / ¾     |
|                      | 45  | 50     | ½ / ¾     |
|                      | 45  | 50     | 1         |
|                      | 50  | 63     | ½ / ¾     |
|                      | 50  | 63     | 1         |
|                      | 50  | 63     | 1 ¼ - 1/2 |
|                      | 60  | 75     | ½ / ¾     |
|                      | 60  | 75     | 1         |
|                      | 60  | 75     | 1 ½ / 2   |
|                      | 75  | 90     | ½ / ¾     |
|                      | 75  | 90     | 1         |
|                      | 75  | 90     | 1 ¼       |
|                      | 75  | 90     | 2         |
|                      | 100 | 110    | ½ / ¾     |
|                      | 100 | 110    | 1         |
|                      | 100 | 110    | 1 ¼       |
|                      | 100 | 110    | 2         |
|                      | 115 | 125    | ½ / ¾     |
|                      | 115 | 125    | 1         |
|                      | 115 | 125    | 2         |
|                      | 125 | 140    | ½ / ¾     |
|                      | 125 | 140    | 1         |
|                      | 125 | 140    | 2         |
|                      | 150 | 160    | ½ / ¾     |
|                      | 150 | 160    | 1         |
|                      | 150 | 160    | 2         |
|                      | 175 | 200    | ½ / ¾     |
|                      | 175 | 200    | 1         |
|                      | 175 | 200    | 2         |
|                      | 200 | 225    | ½ / ¾     |
|                      | 200 | 225    | 1         |
|                      | 200 | 225    | 2         |
|                      | 225 | 250    | ½ / ¾     |
|                      | 225 | 250    | 1         |
|                      | 225 | 250    | 2         |
|                      | 300 | 315    | ½ / ¾     |
|                      | 300 | 315    | 1         |
|                      | 300 | 315    | 2         |
|                      | 325 | 355    | ½ / ¾     |
|                      | 325 | 355    | 1         |
|                      | 325 | 355    | 2         |
|                      | 350 | 400    | ½ / ¾     |
|                      | 350 | 400    | 1         |
|                      | 350 | 400    | 2         |
|                      | 450 | 500    | ½ / ¾     |
|                      | 450 | 500    | 1         |
|                      | 450 | 500    | 2         |

